

Design By Ramos & Bassols

Dua Petra is a surface installation ceiling light where its interior natural slate appearance is combined with the technical elegance of its aluminum outer shell.

Spec sheet













LED 2700 K / 3500 K / Tunable White

Dimming DALI / 0-10V

Installation type Surface CRI>90 2206 lm 98 2700 K / 3500 K / Tunable White LED

Constant Current 500 120~277 V V 50~60 Hz HZ Driver

LED IP20 Multi-volt (1) u 50-60Hz

Application Ceiling Fixtures

1 Box Packaging 21.97 m x 21.97 m x 10.04 m


Gross weight 15.42 Net weight 13.22 Vol. 2.8005











ø 18 3/4"

Any modifications require a minimum order quantity and extra lead time


Lighting effect


General

First layer of basic, general illumination



Photometric Data





Efficiency Coordination System **Total Flux** Maximum Value

69.505 lm/W CG 1796.0 lm 404.43 cd/klm

All of our products come with a two year standard warranty. Check US & Canada Term and Condition sales@vibia.com




Design By Ramos & Bassols



Duo Petra is a surface installation ceiling light where the natural appearance of slate on the inside is combined with the technical elegance of the aluminum casing on the outside. Its large dimensions and diffused lighting help illuminate large spaces with a single electrical connection.

Spec sheet





2700 K / 3500 K / Tunable White

DALI / 0-10V Dimming

LED



Surface Installation type

CRI>90 3958.8 lm 98 2700 K / 3500 K / Tunable White LED

Constant Current 700 120~277 V V 50~60 Hz HZ Driver


LED IP20 Multi-volt (1) u 50-60Hz

Ceiling Fixtures Application

1 Box Packaging 35.28 m x 34.72 m x 9.8 m

Gross weight 41.85 Net weight 37.44 Vol. 6.9465





ø 31"


Any modifications require a minimum order quantity and extra lead time


Lighting effect General

First layer of basic, general illumination



Photometric Data





Efficiency Coordination System **Total Flux** Maximum Value

CG 3580.0 lm 380.69 cd/klm

All of our products come with a two year standard warranty. Check US & Canada Term and Condition sales@vibia.com

272 Fernwood Ave. Edision, NJ 08837. USA



Design By Ramos & Bassols



Spec sheet













LED 2700 K / 3500 K / Tunable White

0-10V / DALI Dimming

Installation type Surface

CRI>90 2206 lm 98 2700 K / 3500 K / Tunable White LED

Constant Current 500 120~277 V V 50~60 Hz HZ Driver


LED IP20 Multi-volt (1) u 50-60Hz

Application Ceiling Fixtures

1 Box Packaging 23.35 m x 30.91 m x 30.91 m

Gross weight 35.24 Net weight 30.84 Vol. 12.9041





Any modifications require a minimum order quantity and extra lead time


a 27 1/2°


Lighting effect General

First layer of basic, general illumination



Photometric Data





Efficiency Coordination System **Total Flux** Maximum Value

46.739 lm/W CG 1201.8 lm 623.60 cd/klm

All of our products come with a two year standard warranty. Check US & Canada Term and Condition sales@vibia.com




Design By Ramos & Bassols



Spec sheet







Any modifications require a minimum order quantity and extra lead time

Finish





93 White RAL 9016

LED 2700 K / 3500 K / Tunable White

Dimming DALI / 0-10V

Installation type Surface

LED CRI>90 2068 lm 109 2700 K / 3500 K / Tunable White

Driver Constant Current 500 120~277 V V 50~60 Hz HZ

LED IP20 Multi-volt (1) us 50-60Hz

Application Ceiling Fixtures

Packaging 1 Box 23.35 m x 30.91 m x 30.91 m


Gross weight 35.24 Net weight 30.84 Vol. 12.9041


Lighting effect General

First layer of basic, general illumination



Photometric Data





Efficiency Coordination System Total Flux Maximum Value 50.193 lm/W CG 1313.6 lm 596.17 cd/klm

All of our products come with a two year standard warranty. Check US & Canada Term and Condition sales@vibia.com